

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

- 1/ (Currently Amended) An assembly, comprising:
a tubular element having a cross-section with a not completely closed contour and comprising at least one slot communicating with an inside of the tubular element;
at least one panel;
at least one pair of fixing elements configured for being mounted on the tubular element, at least one of the fixing elements comprising at least one fixing tab configured for engaging in said at least one slot of the tubular element,
wherein the pair of fixing elements and the panel are configured to enable the panel to be held between the fixing elements, the fixing elements being disposed on either side of the panel.
- 2/ (Original) An assembly according to claim 1, wherein at least one of the fixing elements has a face for bearing against one side of the panel.
- 3/ (Original) An assembly according to claim 1, wherein said at least one fixing tab has a bearing surface suitable for bearing against an inside wall of the tubular element.
- 4/ (Original) An assembly according to claim 1, wherein at least one of the fixing elements has at least two fixing tabs that are offset relative to a central axis of the fixing element.
- 5/ (Original) An assembly according to claim 4, wherein the tubular element has a plurality of slots enabling at least two pairs of fixing elements to be fixed side by side.
- 6/ (Original) An assembly according to claim 1, wherein said at least one fixing tab is configured in such a manner that when it is inserted in the corresponding slot of the

tubular element, the fixing element can pivot relative to the tubular element, at least prior to the panel being put into place.

7/ (Original) An assembly according to claim 1, wherein each of the fixing elements has an opening, and the panel has a orifice, and wherein said openings and said orifice are configured so as to define a passage for the shank of a screw co-operating with a nut.

8/ (Previously Presented) An assembly according to claim 7, wherein at least one of the fixing elements comprises a setback capable of receiving at least one of a nut and the head of a screw.

9/ (Previously Presented) An assembly according to claim 8, further comprising at least one plug configured to be capable of engaging in the setback so as to cover the at least one of the nut and the head of the screw.

10/ (Previously Presented) An assembly according to claim 1, wherein each of the fixing elements is generally in the form of a half-shell.

11/ (Previously Presented) A fixing element for assembling a tubular element and a panel together, the fixing element comprising:

at least one fixing tab suitable for engaging in a slot of the tubular element;
an opening allowing a screw shank to pass through for holding the panel; and
a face for pressing against one side of the panel and comprising stiffening ribs.

12/ (Previously Presented) A tubular element for an assembly according to claim 1, the tubular element having four slots disposed in a checkerboard configuration when observed in a direction perpendicular to the longitudinal axis of the tubular element.

13/ (Previously Presented) An assembly according to claim 8, wherein the setback has a depth that ensures that the at least one of the nut and the head of the screw is received completely in the setback.

14/ (Previously Presented) An assembly according to claim 2, wherein said face has stiffening ribs.

15/ (Currently Amended) An assembly, comprising:
a tubular element having at least one slot;
at least one panel; and
at least one pair of fixing elements not made integrally with the panel and
configured for being mounted on the tubular element, at least one of the fixing elements
comprising ~~at least one of the fixing elements comprising two~~ fixing tabs both for engaging in
at least one slot of the tubular element,

wherein the pair of fixing elements and the panel are configured to enable the
panel to be held between the fixing elements, the fixing elements being disposed entirely on
either side of the panel.

16/ (Currently Amended) An assembly, comprising:
a tubular element being circularly cylindrical and comprising at least one slot;
at least one panel;
at least one pair of fixing elements not made integrally with the panel and
configured for being mounted on the tubular element, at least one of the fixing elements
comprising at least one fixing tab for engaging in said at least one slot of the tubular element,
wherein the pair of fixing elements and the panel are configured to enable the
panel to be held between the fixing elements, the fixing elements being situated on either side
of the ~~panel~~ panel without touching each other.